

## CD-7220 CUSTOMER DISPLAY



The CD-7220 is a top quality customer display in telescope style. The vacuum fluorescence display ensures pin-sharp character definition.

The display retains its optimum legibility even in brightly lit environments.

The display can also optionally draw power from a printer, making it independent of a separate power supply unit.

The CD-7220 is adjustable in height and can be matched to the requirements of any working environment.

### SPECIAL FEATURES

- Vacuum fluorescence display
- 270° rotation option
- Interface RS232 or USB
- Adjustable height
- Two-line display with 20 characters per line

### OPTIONAL

- External power supply 12V

CD-7220

ITEM	CD-7220 Display
Display	Vacuum fluorescent
Display Colour	Blue green
Brightness	700 cd/m2
Interface	RS-232 Serial (D-Sub 9pin) With pass through function, USB with 5V power (do not require power supply)
Power Supply	12V
Power Consumption	5 Watt/ 8 Watt
Backlight MTPT	25.000 Stunden
Viewable Angle	+/- 15°C
Rotation Angle	Max 270°C
Character Front	5 x7 dot matrix, Comma and decimal point
Character Size	9.0mm x 5.25mm
Character Font	96 alphanumerical, 13 sets and one variable
Number of Characters	40 (20 columns x 2 rows) 40 (20 columns x 2 rows) x 2 sides
Dimension	109 mm Base or 42 mm VFD (L) x 230 mm (W) max. 504 mm (H) with long & short pole
Option	Dual Side Display

\*Specification is subject of change without prior notice



Choice of black or white colore



Bright readable characters

