

HANDS-FREE SCANNER


- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.

Z-6070

Hands-Free Dual-Laser Omnidirectional Scanner

The redesigned Z-6070 is spruced up with new features including better cable supports, added voltage protector, more interface options, and a more durable trigger. Like its prior model, the dual laser diodes drastically increase scanning power by doubling up scan lines, broadening scan angle and intensifying scan pattern across scan field. With this state-of-art technology, it is able to deliver the most comprehensive 32-line scan pattern empowering 2,400 scans per second.

- Unique dual-laser technology
- Proprietary Z-SCAN⁺ hardware decode technology
- Large scan field
- Single-line scanning capability
- Easy on-site configuration and upgradeability
- Honored by **Good Design Award 2007**



1. Omnidirectional scan pattern
2. Swiveled stand for forwards and backwards
3. Ergonomic design fits in palm

OPERATIONAL

Light Source	Dual 650 nm visible laser diodes (VLD)
Depth of Field	0 – 216 mm (UPC/EAN 100%, PCS=90%)
Width of Field	45 mm × 2 @ contact; 218 mm @ 216 mm of depth
Scan Line	32
Scan Rate	2,400 scans per second (omnidirectional); 75 scans per second (single-line)
Scan Pattern	8 directions of scan field
Minimum Bar Width	5 mil @ PCS=90%
Print Contrast	30% @ UPC/EAN 100%
Indicator	Two-color LED (blue & red)
Beeper Operation	Programmable tone & beep time
System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, wand

PHYSICAL

Dimension	181.5 × 115.0 × 100.0 mm (with stand)
Weight	307 g (stand excluded)
Cable	Standard 2M straight
Tilt	8° forward; 6° backward

POWER

Input Voltage	5 VDC ±10%
Power Consumption	1.35 watts
Operating Current	270 mA

REGULATORY

Laser Class	CDRH Class IIa; IEC 60825-1: Class 1
EMC	CE & FCC DOC compliance, VCCI, BSMI

ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 95% RH (non-condensing)
Light Level	Max. 4,000 Lux (fluorescence)
Drop Durability	Designed to withstand 1M drops

DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF, Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, DTF, JAP, Code 11, RSS 14, RSS Limited, RSS Expanded
------------	--

